

FIBERGLASS, POLYCARBONATE & PVC SHEETING

Recommended Care

Handling, Storage and Cleaning

- Store sheets on a flat surface in a well-protected and shaded area, out of direct sunlight. Stacked sheets stored in the sun will cause heat build-up and possible distortion, even if covered. If damage occurs in this situation, warranty is void.
- Sheeting should not be dragged across objects or other products as it may affect the performance and aesthetics of the roof sheet, as with dragging objects and other products across the sheeting.
- Sheeting that becomes wet in bundles and is required to be stored should be separated and dried prior to storage.
- Prevent moisture getting between stored sheets as this may cause whitening.
- Care should be taken when loading the translucent roofing onto the roof to avoid bending or distortion of the sheet.
- Clean sheets regularly with warm soapy water (mild detergent) and a soft sponge. Take care not to scratch the sheet. Hose down thoroughly.

Chemical Properties

Chemicals such as Methylated Spirits, Benzene, Petrol, Ketones, Acetone, Phenols, Chlorinated and Aromatic Hydrocarbons, Petroleum-based Paints, abrasive cleaners and solvents will affect fibreglass, polycarbonate and PVC roof sheeting. Use of such chemicals on Alsynite sheeting will void warranties.

ALSYNITE HEAD OFFICE: Freephone 0800 257 964
Hamilton 07 850 5088

DISTRIBUTION CENTRES: Palmerston North 06 356 5384
Christchurch 03 348 3375
Invercargill 03 214 6002